

Tally DASCOM T2600+



The Tally Dascom 2600 printers are featured, reliable, and stylish machines. Performance, workload, maintainability, and excellent price ensure it is your only acceptable choice.

Continuous and cut forms fed quickly and easily to the front of the printer. This ensures a reliable paper transportation, even on 6-part stock.

The operator does not have to fumble over or around the printer to gain access to rear located tractors.

High performance at low cost

- Its 680 cps print speed allows up to 20.000 pages per month
- Excellent print quality
- Ethernet parallel and USB interface as standard
- User-friendly interface with backlight illuminated LCD display

The printer operates with the highest reliability and performance and the least user intervention.

A lower acoustic rating results in a printer which is half as quiet as other competitive models.

Using the built-in Intelligent Mail® Barcode it is possible to get the best US Postal Service rates available



Intelligent Mail Barcode Sample

Available configurations:

T2600+ Standard Product - 80 columns

Tally DASCOM T2600+

| | |
|----------------------------------|--|
| Print Speed | 680 cps (Fastest Draft); 500 cps (HS-Draft), 333 cps (Draft), 111 cps (LQ) at 10 cpi |
| Resolution | Up to 360 x 360 dpi (ESC/P Emulation only) |
| Character Density | 10, 12, 15, 17.1, 20 cpi |
| Line Density | 2, 3, 4, 6, 8, 12 lpi |
| Printhead Life | 500 million strokes per pin |
| Standard Memory | 256 kB |
| Standard Connectivity | Parallel (Bi-Directional IEEE 1284) Ethernet (10/100 Base T, Ipv6) and USB 2.0 |
| Optional Connectivity | RS-232 Serial |
| Emulations | IBM ProPrinter XL24, Epson ESC P/2, MTPL + Barcode + LCP Epson FX 9 needle Emulation |
| Optional Emulations | Neg TOF, Oki Data Barcode |
| Fonts | HS Draft, Draft, Courier, Roman, Sans Serif, Prestige, Script, OCR-A/B, 14 Barcodes and large character printing |
| Consumables | Ribbon: 9 million characters |
| Standard Paper Handling | One tractor useable as push (front or rear) or pull (top) version, continuous paper with straight paper path and park position, cut sheet front insertion, tear or front off |
| Optional Paper Handling | Additional Push Tractor (rear) |
| Number of Copies | Push tractor front: 1 original + 5 copies; Pull tractor top: 1 original + 1 copy; Cut sheet: 1 original + 5 copies |
| Paper Type | Cut sheets, continuous forms, multi-part forms |
| Paper Weight | 60 – 120 g/m ² |
| Paper Size | Width: 3" to 11" (76 mm – 278 mm) Length: 3" to 23.6" (76 mm – 600 mm) |
| Physical Weight | 18.9 lbs (Approximately 8.6 kg) |
| Physical Size (W x D x H) | 18" x 10.4" x 7.9" (458 x 265 x 200 mm) |
| Acoustic | 55 dB(A) |
| Power Voltage | 120 V or 240 V (auto-switching) |
| Power Consumption | 40 Watts while Printing; less than 10 Watts while in power save |
| Temperature/Humidity | 50 °F – 104 °F (+10 °C to +40 °C) 10% to 85% RH (not condensing) |
| Workload | Up to 20,000 pages per month |
| Reliability MTBF | 15,000 hours |
| Drivers | Windows 7/8/10 and Server 2008/2012 (32/64 Bit); SAP |
| Warranty | 1 Year Return to Depot |

DASCOM Americas
 34 Lakeview Court
 Verona, Virginia, 24482 . USA.
 Tel: +1 (877) 434-1377
www.dascomamericas.com
info.us@dascom.com

THERMAL PRINTERS

MOBILE PRINTERS

MATRIX PRINTERS

POS PRINTERS

ID PRINTERS